





Panasonic

VIDEO DOOR INTERCOM SYSTEMS
Effective Date August, 2005
Supersedes all Previous Price Lists

VIDEO DOOR INTERCOM SYSTEMS PRODUCT CATALOG



Model Number	Description	Per Master Carton		UPC Code 0-37988-
		Units	Weight	
VIDEO DOOR INTERCOM MONITORS				
VL-GM201A 	VIDEO DOOR INTERCOM MONITOR Supports 1 monitor, 1 camera and 1 door opener connection. Compatible with VL-GC002A-W, VL-GC001A-S and VL-GC001A-N Door Cameras only. Also supports one connection to most Panasonic Telephone system models (Please refer to Chart 1 for telephone system compatibility) Features <ul style="list-style-type: none"> • 2.5" Color LCD Display • Hands-free or Press to Talk Operation • 5 Step Brightness Control • Wall or Desk Mountable 	3	3.53 lbs.	82504-2
VL-GM301A 	PREMIUM VIDEO DOOR INTERCOM MAIN MONITOR Supports 3 monitors (1 main monitor and 2 expansion monitors VL-GM001A), 2 cameras and 2 door opener connection. Compatible with VL-GC002A-W, VL-GC001A-S and VL-GC001A-N Door Cameras only. Also supports two connections to most Panasonic Telephone system models (Please refer to Chart 1 for telephone system compatibility) Features <ul style="list-style-type: none"> • 3.5" Color LCD Display • 3 Step Ringer Control • Hands-free or Press to Talk Operation • 5 Step Brightness Control • Video Out Jack (RCA Jack) • Wall Mountable (Surface or Recessed) 	3	3.75 lbs.	82500-4
VL-GM001A 	MULTI VIDEO DOOR INTERCOM EXPANSION MONITOR For use with the VL-GM301A Premium Video Door Intercom Monitor only. Maximum of two can be installed. Features <ul style="list-style-type: none"> • 3.5" Color LCD Display • 3 Step Ringer Control • Hands-free or Press to Talk Operation • Wall Mountable (Surface or Recessed) 	3	3.75 lbs.	82501-1
VIDEO DOOR INTERCOM ACCESSORIES				
VL-GT001A 	DESK MOUNTING KIT FOR THE VL-GM201A For mounting the VL-GM201A on a desk or counter.	3	.66 lbs.	82507-3
VL-GT001A 	RECESSED MOUNTING KIT FOR THE VL-GM301A/001A For recessed mounting the VL-GM301A and the VL-GM001A in a wall.	3	2.20 lbs.	82503-5









Model Number	Description	Per Master Carton		UPC Code 0-37988-
		Units	Weight	
VIDEO DOOR INTERCOM CAMERA				
VL-GC002A-W 	DOOR CAMERA Plastic body door camera. Includes an adjustable camera, speaker, microphone, illuminated button and mounting hardware. Compatible with VL-GM201A and the VL-GM301A Video Door Intercom systems only.	3	1.10 lbs.	82502-8
VL-GC001A-S 	PREMIUM DOOR CAMERA (SILVER) Includes an adjustable pinhole camera, speaker, microphone, illuminated button in a silver color aluminum housing. Mounting hardware included. Compatible with VL-GM201A and the VL-GM301A video door intercom systems only.	3	1.10 lbs.	82506-6
VL-GC001A-N 	PREMIUM DOOR CAMERA (GOLD) Includes an adjustable pinhole camera, speaker, microphone, illuminated button in a gold color aluminum housing. Mounting hardware included. Compatible with VL-GM201A and the VL-GM301A video door intercom systems only.	3	1.10 lbs.	82505-9

CHART #1		
PBX COMPATIBILITY CHART		
Panasonic PBX System	Compatibility	Required Doorphone Card
KX-TA308	Yes	Built in
KX-TA624	Yes	KX-TA62460
KX-TA1232	Yes	KX-TA123260
KX-TA824	Yes	KX-TA82460
KX-TD308	Yes	Built in
KX-TD816	Yes	KX-TD160
KX-TD1232	Yes	KX-TD160
KX-TAW848	Yes, Requires software upgrade	KX-TAW84861
KX-TDA50	Yes, Requires software upgrade to 2.0 or higher	KX-TDA5161
KX-TDA100	Yes, Requires software upgrade to 2.01 or higher	KX-TDA0161
KX-TDA200	Yes, Requires software upgrade to 2.01 or higher	KX-TDA0161
KX-TD500	No	

MONITOR FEATURE LIST AND SPECIFICATIONS

Model Number		VL-GM301A	VL-GM201A
Main Feature		Premium Monitor	Monitor
Design			
System Configurations		up to 3 monitors, 2 cameras	1 monitor, 1 camera
Monitor	LCD Size	3.5"	2.5"
	Communication	Hands-free or Press-to-talk	
	Answer by Voice	-	✓
	Ringer Tone	✓ (5)	-
	Ringer Volume	3 steps (1~3)	
	Receiver Volume	3 steps	-
	Intercom (Monitor to Monitor)	✓	-
	Camera Capability	2	1
	Camera On/Off	✓	-
	Voice Call	✓	✓
	Door Strike	✓ (2 circuits)	✓ (1 circuit)
	Video Out	✓	-
	Alarm Out Put	✓	-
	PBX Connect	✓ (2 circuits)	✓ (1 circuit)
	Indication Time of Video Monitor		
	-Outside Call (Calling)	Approx. 30 second	
	-Monitoring	1 minute	
	-Outside Call (Talking)	1 minute 30 seconds	
	-Outside Call (Press to Talk)	1 minute	
	Brightness	5 steps	
	Installation	Flush Mount/Surface Mount	Surface Mount/Desk Mount
	Dimensions	6.4"W x 1.25"D x 5.5"H	5.3"W x 1.25"D x 5.5"H
	Material	ABS	
Power Consumption	Stand-by 44mV, Operation 450mV (DC24V)	Stand-by 30mA, Operation 420mA (DC24V)	
Operating Enviroment	32F to 104F		
Length of Cable	Monitor Power Supply	98ft (Fire Alarm Cable)	
	Main Monitor to Camera	328ft (CAT3 Cable)	
	Monitor to Monitor	100m (CAT3 Cable)	-

DOOR CAMERA FEATURE LIST AND SPECIFICATIONS

	VL-GC001A-N	VL-GC001A-S	VL-GC002A-W
Design			
Color	Gold	Silver	White
Material	Aluminum		Plastic
View Area			
- Horizon 50cm from Camera	Approx. Left&Right 22.83°_60°_AngleChange 25.59"(60°)		45° 98°
- Vertical 50cm from Camera	Approx. Upside 16° 46°		31° 77°
Angle Adjustment	Left & Right		Left & Right & Up
Operating Environment	14° F ~ 122° F		
Power Supply	From Monitor		
Lighted Key	✓ Blue		✓ Green
Camera Device	CCD 250k pixels		
Minimum Brightness	Approx. Lux/19.68" from Camera		
Infrared Camera	✓		
Splash Resistant	✓		
Dimensions	W3.54" x D1.3" x H6.49"		W3.85" x D1.69" x H5.11"
Weight	.73 lbs.		.66 lbs.

NOTES

WARRANTY DATA – COMPLETE TERMS OF THE WARRANTY ARE SET FORTH ON WARRANTY CARDS PACKED WITH THE PRODUCT AND AVAILABLE FOR THE CUSTOMER'S EXAMINATION FROM THE DEALER PRIOR TO PURCHASE.

LIMITED WARRANTY

ALL PANASONIC VIDEO DOOR INTERCOM COMPONENTS
1 YEAR PART & LABOR

ALL OF THE ABOVE SUBJECT TO TERMS OF WRITTEN WARRANTY.

All shipments F.O.B. from our warehouse.

All Orders subject to our acceptance.

Prices quoted are subject to change without notice.

Units, Weights and Specifications are subject to change.

NO RETURNS without prior approval in writing by our

Regional Office.

For warranty service, please send product, including detailed description of problem, to the CSD Repair Center listed below.

CSD Service Centers

Panasonic Service Center
1225 Northbrook Parkway
Suite 1-216
Suwanee, GA 30024
Phone: (770-338-6550)
Fax: (770-338-6557)
e-mail: btsservice@us.panasonic.com

MINIMUM ORDER QUANTITY POLICY

ALL ORDERS MUST BE IN MASTER CARTON QUANTITY INCREMENTS ONLY!

MINIMUM ORDER QUANTITY OF SIX (6) UNITS FOR ALL PRODUCTS.
EXCEPT:

MINIMUM ORDER QUANTITY OF THREE (3) UNITS FOR:
HYBRID TELEPHONE SYSTEM COMPONENTS

NO MINIMUM ORDER QUANTITY FOR:
ACCESSORIES

WHEN PRODUCT CATEGORIES ARE MIXED ON AN ORDER, THE CATEGORY WITH THE HIGHEST MINIMUM WILL DETERMINE THE MINIMUM ORDER QUANTITY FOR THAT ORDER.

Panasonic

ideas for life

Panasonic Consumer Electronics Company
Division of Panasonic Corporation of North America

Executive Offices

Three Panasonic Way 4A-1, Secaucus, New Jersey 07094 • (201) 348-7000

Panasonic Customer Call Center

9 am - 9 pm (EST) Monday through Friday; 9 am - 7 pm (EST) Saturday and Sunday

1-800-211-PANA

consumerproducts@us.panasonic.com

www.panasonic.com/csd